

MATERIAL SAFETY DATA SHEET

Product: WeatherSmart™

Effective: January 3, 2006
Supercedes: New

Page 1 of 3

SECTION I

Company Name
Fortifiber Corporation

Emergency Telephone No.
508-222-3500

Address: 55 Starkey Ave., Attleboro, MA 02703

Chemical Name & Synonyms
N/A

Trade Name & Synonyms
WeatherSmart™

Chemical Family
Polyolefin

Formula
N/A

SECTION II - HAZARDOUS INGREDIENTS

In the solid state the material is not considered a hazardous material as defined by 21CFR 1900.1210 (OSHA Hazards Communications Law) paragraph (b) (5) (iv). This product is supplied in compliance with TSCA reporting requirements.

SECTION III - PHYSICAL DATA

Boiling Point (°F.)
N/A

Specific Gravity (Water=1)
< 1.0

Vapor Pressure (mmHg.)
N/A

Percent, Volatile by Volume (%)
N/A

Vapor Density (Air=1)
N/A

Evaporation Rate(Butyl Acetate=1)
N/A

Solubility in Water: Negligible

Appearance & Odor: Non-woven polyolefin fabric coated on one side with a polyolefin-based coating.

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

Flash Point N/A Method N/A Flammable Limits N/A LeI N/A/VeI N/A

Extinguishing Media: Water spray, CO2, foam, dry chemical

Special Fire Fighting Procedures: Wear self-contained breathing apparatus and protective clothing to prevent contact with skin and eyes.

Unusual Fire and Explosion Hazards: Refer to NFPA Pamphlet No.654, "Prevention of Fire and Dust Explosions in the Chemical, Dye, Pharmaceutical and Plastics Industries".

MATERIAL SAFETY DATA SHEET

Product: WeatherSmart™

Effective: January 3, 2006
Supercedes: New

Page 2 of 3

SECTION V - HEALTH HAZARD DATA

Threshold Limit Value Not established

Effects of Overexposure

INHALATION: None in solid state form. In molten form, irritating vapors may be released.

EYES: Low hazard for normal industrial handling.

SKIN: Molten material will produce thermal burns.

Emergency and First Aid Procedures

SKIN: If burned by contact with molten material, cool as quickly as possible and see a physician for treatment of burn.

Note to Physicians: Burns should be treated as thermal burns. The plastic will come off as healing occurs; therefore, immediate removal from the skin is not necessary.

SECTION VI - REACTIVITY DATA

Stability: Stable X Unstable

Conditions to Avoid: Keep away from direct flame. Avoid exposure to strong oxidizing agents (such as nitric and sulfuric acid, halogen and chlorinating agents) or strong bases.

Hazardous Polymerization: May Occur Will not Occur X

Hazardous Decomposition Products: As with any organic material, combustion will produce carbon monoxide, acrolein, and aldehydes.

SECTION VII - SPILL OR LEAK PROCEDURES

Steps to be Taken in Case Material is Released or Spilled: N/A

Waste Disposal Method: Incineration or landfill. Observe all federal, state and local laws concerning health and the environment.

SECTION VIII - SPECIAL PROTECTION INFORMATION

Respiratory Protection N/A

Ventilation: - Local Exhaust N/A
Special N/A

Mechanical N/A
Other N/A

Protective Gloves
N/A

Eye Protection
Safety glasses, ANSI Std. 287.1

Other Protective Equipment
None

Work/Hygienic Practices
Use proper lifting techniques to prevent back injury

MATERIAL SAFETY DATA SHEET

Product: WeatherSmart™

Effective: January 3, 2006
Supercedes: New

Page 3 of 3

SECTION IX - SPECIAL PRECAUTIONS

Precautions to be Taken in Handling and Storing Other Precautions N/A
Do not store near open flame.
Use reasonable care and caution in handling.

SECTION X – REGULATORY

SARA / TITLE III

This product does not contain a toxic chemical for routine annual toxic chemical reporting under section 313 (40 CFR 372)

DISCLAIMER: The information provided herein is believed to be accurate but is not warranted to be whether it originated with Fortifiber Corporation or not. Much of the information contained in this Material Safety Data Sheet originates from suppliers: this information cannot be warranted by Fortifiber Corporation to be correct or appropriate for the recipient's intended use. Recipients are advised to confirm in advance of need that the information is current, applicable and suitable to their circumstances.
